

editor's choice

THE AHG-T42 GAS TANKLESS WATER HEATER

is the only model on the market that fits the standard 1/2" natural or propane gas supply line found in most homes. Ideal for smaller households, the heater has a small footprint and delivers unlimited hot water on demand with no standby loss. It is also suited for supplemental applications such as commercial dish washing. It is manufactured with oxygen-free copper to reduce lime scale build-up and for higher heat exchange efficiency. It meets the EPA's EnergyStar requirements qualifying homeowners for state and federal tax credits.

AHI Technologies

CIRCLE 101 ON INQUIRY CARD



THE TRANQUILITY 22 DIGITAL SERIES GROUND-SOURCE HEAT PUMP

features a two-stage compressor, EnergyStar tier 3 efficiency, variable speed fan, communicating digital controls and "plug-and-play" functionality. It also has a small footprint, making it suitable for installation in tight spaces. It is available in vertical and horizontal configurations in capacities of 24,000, 30,000, 36,000, 42,000, 48,000 and 60,000 Btuh.

ClimateMaster

CIRCLE 106 ON INQUIRY CARD



THE MONOGLIDE HAND SHOWER

is a four-function hand shower controlled by a simple sliding button. The non-slip button allows the user to select from wide spray, aerated spray, massage spray and power mist spray, all with easy one-hand operation. It is offered with two flow-rate options: standard model with 2.5 GPM or a water-saving model with a 2.0 GPM flow rate.

American Standard

CIRCLE 108 ON INQUIRY CARD



THE SUNNECTOR SOLAR ASSEMBLIES AND HARNESSES LINE

includes whip and jumper assemblies, parallel circuit array harnesses, home run harnesses and custom solutions to meet the needs of complex solar projects.

Cooper Interconnect

CIRCLE 109 ON INQUIRY CARD



THE GEOCAL GEOTHERMAL MANIFOLD

ships pre-assembled. Designed for ground-source geothermal loops, it offers an alternative method of piping parallel earth loops, bringing all circuits to a common manifold station without labor-intensive fusion welding. Optional 3/4" or 1" QuickSetter balancing valves are offered.

Caleffi

CIRCLE 110 ON INQUIRY CARD



THE WARMBOARD-R RADIANT HEATING PANEL

is a 1 1/16"-thick structural panel that provides the same performance as the company's 1 1/8"-thick radiant subfloor panel. The slimmer profile makes it ideal for remodels and renovations where the full structural support of the 1 1/8" panel is not needed. It can also be used as a ceiling panel for radiant cooling applications.

Warmboard

CIRCLE 102 ON INQUIRY CARD



THESE CONFIGURABLE RAINWATER HARVESTING SYSTEMS

for commercial and residential applications can reduce water consumption by as much as 65%. They are offered in storage capacities from 200 to over two million gal., and manage the filtration, storage, distribution and treatment functions.

BRAE

CIRCLE 103 ON INQUIRY CARD

THE ALTO 1.28 HIGH EFFICIENCY TOILET

is able to thoroughly flush 600 grams with only 1.28 gal. of water, thanks in part to a 3" hybrid flush valve. It comes in three configurations: ADA, elongated and round front. It features hydraulic enhancements to help reduce clogs.

Mansfield

CIRCLE 104 ON INQUIRY CARD



THE ZONE SENTRY VALVE

uses microcircuit-based logic to control gear-driven electronically-actuated ball valve to control liquid flow. The advanced design uses 93% less energy than common zone valves while delivering greater flow capacity, shutoff pressure rating and easier installation. It is designed primarily for baseboard, fan coil, radiator, convactor, heat pump and radiant applications.

Taco

CIRCLE 105 ON INQUIRY CARD



THE CYPRESS SERIES GEOTHERMAL COMFORT SYSTEM

provides forced-air heating and cooling, hydronic heating for radiant floors and a hot water assist option that can provide homeowners with free supplemental domestic hot water. It is available in 3- to 6-ton capacities.

GeoStar

CIRCLE 107 ON INQUIRY CARD