

PROTECTOR®

NO-OVERFLOW TOILET



GET PEACE OF MIND IN A STYLISH NO-OVERFLOW TOILET.

CONCEALED SECONDARY DRAIN PROVIDES OVERFLOW PROTECTION

- 1.6 gpf / 6.0 lpf low water consumption
- Prevents clogged toilet from overflowing
- No unsightly holes, overflow system is hidden within the bowl
- Highly engineered PuraClean™ glaze makes the bowl easy to clean and bacteria resistant
- Reliable and simple to install
- SmartHeight™ bowl for comfortable sitting and standing



MANSFIELDPLUMBING.COM

PROTECTOR®

NO-OVERFLOW TOILET

ELIMINATE OVERFLOW WORRIES

UNIQUE SECONDARY DRAIN

Concealed within the bowl, a back-up drain directs excess water into the drain line.

IMPROVED STYLING

No unsightly holes, overflow system is hidden within the bowl.

3-INCH FLUSH VALVE DESIGN

3-inch opening delivers higher velocity for more powerful flush action—800 gram MaP*.

EASY-TO-CLEAN SURFACE

Highly engineered PuraClean™ glaze finish is 48% smoother** than the nearest competitor, making the bowl easy to clean and bacteria resistant.



SIMPLE TO INSTALL CONSTRUCTION

Fast, easy tank installation thanks to our SmartFasten™ System.

ERGONOMIC SMARTHEIGHT™ BOWL

16-1/2-inch tall bowl is just the right height to make sitting and standing more comfortable.



MODEL #	DESCRIPTION	CODES/STANDARDS
1384-1386 (shown)	SmartHeight™, elongated front two-piece toilet. Less toilet seat and supply.	 
1384	SmartHeight™, elongated front toilet bowl only. Less toilet seat.	
1386	Tank and cover only, with left hand, front-mount, metal trip lever. Less supply.	
*1384CTK	Elongated front, SmartHeight™ complete toilet kit. Includes toilet seat, tank and bowl, flange bolts, wax ring with polyethylene flange and instructions. Less supply.	

All models are white with 12" rough-in and offer the Mansfield limited lifetime warranty on construction and 1-year limited warranty on working parts.

*Maximum Performance (MaP) testing is an independent testing protocol developed by public utilities to rate toilet efficiency and flush performance in the removal of solid waste.

MaP grades toilet performance on a scale of 0-1,000. ** Mansfield Internal RIQ testing 2015