## 

# **RESTORE<sup>™</sup> WALK-IN TUB**

### **FEATURES**

- 51 1/2 ' x 30' x 40' Walk-in Tub
- Taller than standard tub with scuplted 17' high seat (ADA), allows the bather to remain in an upright position while being completely submerged in water
- Water-tight, inward swinging door with Lifetime Guarantee on the seal gives users with limited mobility a safe and easy entry and exit
- Non-rusting door hinge and handle
- · Easy door locking system
- · Available in white
- · Rich, high gloss finish and slip resistant floor
- · Adjustable one-inch steel frame with adjustable feet
- Replaces standard size tub with right or left hand drain and fits through a standard 32' bathroom doorway
- Removable access panels allow for complete access to components
- Available in Soaker, Whirlpool, Air Bath and Combinations in both left and right hand drain options
- Outstanding Protection 10 year warranty on shell, 5 year warranty on all factory installed components



#### MODELS

MODEL #	DESCRIPTION	APPROX. WT.
8010	Whirlpool - Right Hand	225 lbs.
8110 Whirlpool - Left Hand		225 lbs.
8210	8210 Bathtub - Right Hand	
8310	Bathtub - Left Hand	195 lbs.
8410 Air Bath - Right Hand		215 lbs.
8510 Air Bath - Left Hand 215 lbs		215 lbs.
8610	Combination - Right Hand	255 lbs.
8710	Combination - Left Hand	255 lbs.

### **FEATURES & OPTIONS**

#### **SOAKING TUB**

- Tall, standard tub equipped with a water-tight door that allows you to enter effortlessly
- Cable waste and overflow standard feature

#### AIR BATH

- 16 strategically placed air jets with check valves
- Hygienic purge feature begins the drying process
- Raised air button easily turns blower on and off
- 120V, 8 amp, blower with heating element
- Cable waste and overflow standard feature

#### WHIRLPOOL

.

- 5 multi-directional hydrotherapy jets, each with individual volume control
- Inline heater to maintain warm water temperature
- Electronic, color coded keypad for easy operation
- 120V, 9 amp pump
- Cable waste and overflow standard feature

#### **COMBINATION BATH**

Combines the air and whirlpool jets in a single bath for the best of both worlds

## 

# **RESTORE<sup>™</sup> WALK-IN TUB**

### **SPECIFICATIONS**

DIMENSIONS	51 ½' x 30' x 40'	ELECTRICAL REQUIREMENTS	Air Bath: One dedicated, 120V, 20 amp
MATERIAL Construction	Marine Grade Fiberglass Outer finish is a double hand applied gelcoat. Frame is one inch powder- coated steel. All hardware and door mechanisms are finest quality stainless		GFCI protected circuit. <b>Whirlpool:</b> Two separate, dedicated, 120V, 20 amp GFCI protected circuits. <b>Combination:</b> Three separate dedicated, 120V, 20 amp GFCI protected circuits.
	steel.	NUMBER OF JETS	Whirlpool: 5 jets Air Bath: 16 jet holes
PUMP MOTOR	Whirlpool: 120V, 9 amp	WATER CAPACITY:	40 - 50 gallons (with bather)
AIR BLOWER	Air bath: 120V, 8 amp	FLOOR LOADING:	450 lbs.
INCLUDES	Wall bracket kit, end panel, front panel	WARRANTY:	10 - Year warranty on the shell
	and cable drain. Nailing flange kit, additional end panel and extension box		5 - Year warranty on factory components
	optional.		Lifetime warranty on the door seal

### **TECHNICAL INFORMATION**

Note: Product is manufactured to comply with industry standards. Rough-in dimensions may vary +/- ¼".

